



PERSON-PORTABLE GC-MS CHEMICAL IDENTIFIER

FLIR GRIFFIN™ G510

The FLIR Griffin™ G510 Gas Chromatograph Mass Spectrometer (GC/MS) is a versatile, person-portable chemical identifier. It complements presumptive techniques used during emergency missions, by enabling responders to analyze all phases of matter (liquid, solid, vapor) and by performing rapid field- confirmation of chemical hazards. The integrated heated sample probe enables hot zone operators to identify vapor-phase chemical threats within seconds when operated in Survey Mode. The integrated split/splitless injector allows for environmental, forensic, and hazardous material sampling via syringe injection of organic liquids. The 9" on-board touchscreen displays guided user prompts and can be operated while wearing full personal protective equipment (PPE) downrange. It is built with an IP65-rated enclosure for harsh environments and supports passive defense, interdiction, elimination, and consequence management missions. Long-lasting, on-board batteries ensure every mission is supported from beginning to end.

www.flir.com/G510



MASS SPEC PERFORMANCE REDEFINED

Confidently identify unknowns and take action with guided prompts and simple threat alarms

- Laboratory level, gold-standard linear quadrupole mass analyzer
- Full NIST and SWGDRUG on-board libraries provide confirmatory identification and analysis of trace compounds, unknown chemicals, and mixtures
- Simple on-board touchscreen with navigation assistant and Method Selector tool
- Visual and audible alarm confirmation with limited data interpretation
- On-board WiFi and GPS assist in maintaining result defensibility
- · Remote monitoring and control with WiFi hotspot



ULTIMATE CHEMICAL DETECTION TOOLBOX

Versatile in-field sampling options for vapor, liquid, and solid samples

- Vapor sampling probe with rapid-response survey mode
- Integrated split/splitless liquid injector accepts direct injection of organic liquids
- Available Prepless Sample Introduction (PSI) Probe, Sample Prep Kit (SPK), and Touch-And-Go (TAG™) capability for direct analysis of solid samples
- Effortlessly links with SPME and headspace sample collection tools
- High-fidelity, low thermal mass (LTM) GC column for unsurpassed resolution in challenging environments



BUILT FOR EVERYONE, BUILT FOR EVERYWHERE

Completely self-contained and mission-ready from the field to the lab

- IP65-rated, dust-tight and spray-resistant
- Built-in active pumping system eliminates need for an external service module
- Integrated carrier gas, batteries, and training reference videos
- Simple field maintenance activities for increased uptime
- Extensive training, service, and reachback options available
- Optional vehicle mount kit for shock and vibration protection during off-road or harsh transport

SPECIFICATIONS

Griffin G510

Technology

Dimensions (L x W x H)

Gas Chromatography/Mass Spectrometry (GC/MS)

32 to 104 °F (0 to 40 °C); <95% relative humidity

13.25 x 13.25 x 15.75 in (33.7 x 33.7 x 40 cm) - includes batteries, carrier gas, and vacuum system

Road-Ready Version: 16.7 x 14 x 15.2 in (with G510 installed)

Off-Road Version: 16.7 x 17.5 x 16.2 in (with G510 installed)

Weight 36 lbs (16.3 kg) - includes batteries, carrier gas,

and vacuum system

-13 to 131 °F (-25 to 55 °C)

Optional Vehicle Mount Kit

(LxWxH)

Operating Temp / Humidity

Storage Temp

Decontamination

Power Supply

Battery Life

Start Up Time Calibrant

Display

Carrier Gas

System Interface

9" Multitouch Color Display

(1280x720 WVGA;1300 nits brightness)

Alerts Audible and visual (touchscreen and handheld probe)

GSS Level 1 Touch; multiple user levels Software

2 x USB 2.0, Bluetooth 4.0, WiFi 802.11n, Ethernet via USB, Communication

integrated GPS

Internal ≥128GB SSD Data Storage

Training Requirements 2 hours basic operation; 8 hours Operator Certification

Sampling & Identification

Sample Phase

Threats

Sample Introduction

Solid, liquid, and vapor

Heated Sample Probe (included standard):

- Vapor survey mode via Membrane Introduction Mass Spectrometry (MIMS) Inlet
- · Vapor confirmation via Internal Dual-Bed Preconcentrator

Split/splitless injector (included standard) accepts:

- Direct liquid sampling (organic solution) via syringe
- Liquid extraction via SPME fiber or PSI-Probe w/ Gerstel Twister™ *
- Solid PSI-Probe™ thermal separation via TAG™ *

Sample Prep Kit (SPK)

Simplified analysis of solids and liquids

Detects and identifies trace-level explosives, narcotics like Fentanyl and its analogues, A-series and Novichok CWAs, TICs,

environmental pollutants, and other chemicals

Standard Reference Database

NIST/EPA/NIH Mass Spectral Library, SWGDRUG Mass Spectral Library, and GriffinLib Mass Spectral Library included, with instant updates available

*optional accessories

Sampling & Analysis

Full identification in 4-15 minutes for most chemicals; identification within seconds (near real-time) when operating in Survey Mode

Electron Impact Ionization; non-radioactive ionization source

Self-contained miniature turbomolecular & diaphragm pumps

PPM (parts per million) - PPB (parts per billion). Note: PPT (parts

per trillion) for vapor analysis with extended sampling time.

Linear quadrupole mass filter

15-515 m/z; 0.7 amu @ FWHM

Electron Multiplier

7 decades

Mass Spectrometer

Mass Analyzer Type

Mass Range / Resolution

Ionization Type / Source

Vacuum System

Dynamic Range

Detection Limit

100-240V 50-60Hz (220 W max); 19V (DC); 2 x #2590 @ 15V Li

Ion batteries (included)

Sealed for Survey Mode operation in hot-zone; IP65-rated

4 hrs in Survey Mode, 2 hrs in Confirmation Mode; hot swappable

15 minutes to full operation from cold

enclosure is dust-tight and spray-resistant

On-board FC-43 (Perfluorotributylamine)

On-board helium: external helium connector, automatic switching (Hydrogen capable)

Gas Chromatograph

LTM-GC Column

Temperature Range

DB-5MS (15 m x .18 mm x .18 um); others available

Programmable 40 to 300 °C; ramping of 100 °C/min

Specifications are subject to change without notice. For the most up-to-date specs, go to www.flir.com





Method Selector Tool



GSS Touch Chemical Identification Result



Trace-level detection of narcotics like Fentanyl and its analogues

HEADQUARTERS

FLIR Systems, Inc. 1201 S. Joyce Street Suite C006 Arlington, VA 22202 USA PH: +1-877-692-2120

DETECTION SALES, APAC

FLIR Detection, Inc. 10 Kallang Avenue #09-10 Aperia Tower 2 Singapore 335910 PH: +65-6822-1596

DETECTION SALES, EMEA

FLIR Detection, Inc. Luxemburgstraat 2 2321 Meer Belgium PH: +32 (0) 3665 5106 detection@flir.com

www.flir.com NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2021 FLIR Systems, Inc. All rights reserved. 03-09-21

21-0317-DET-Update G510 Datasheet-Ltr

